

Postfix

Ictseng (2020-2022, CC-BY)

? (?-2019)

國立陽明交通大學資工系資訊中心


Computer Center of Department of Computer Science, NYCU

Postfix

- Postfix v3.6.x
 - Latest stable release: 3.7.0 (Feb 2022)
 - /usr/ports/mail/postfix
 - pkg install postfix
- <http://www.postfix.org>
 - <http://www.postfix.org/documentation.html>


Role of Postfix

- MTA that
 - Receive and deliver email over the network via SMTP
 - Local delivery directly or use other mail delivery agent
 - <http://www.postfix.org/OVERVIEW.html>




Postfix Architecture

- Modular-design MTA
 - Not like sendmail of monolithic system
 - Decompose into several individual program that each one handle specific task
 - The most important daemon: master daemon
 - Reside in memory
 - Get configuration information from `master.cf` and `main.cf`
 - Invoke other process to do jobs
- Major tasks
 - Receive mail and put in **queue**
 - Queue management
 - Delivery mail from queue



Postfix Architecture – Message IN

- Four ways
 - Local submission
 - postdrop command
 - maildrop queue
 - pickup daemon
 - cleanup daemon
 - Header validation
 - Address translation
 - incoming queue
 - Network submission
 - smtpd daemon
 - Local forwarding
 - Resubmit for such as .forward
 - Envelope "to" is changed
 - Notification
 - Notify admin when error happens




Postfix Architecture – Queue

- Five different queues
 - incoming
 - The first queue that every incoming email will stay
 - active
 - Queue manager will move message into active queue whenever there is enough system resources
 - Queue manager then invokes suitable DA to delivery it
 - deferred
 - Messages that cannot be delivered are moved here
 - These messages are sent back either with bounce or defer daemons
 - corrupt
 - Used to store damaged or unreadable message
 - hold
 - Requested by admin (manually or automatically)
 - Stay in queue until admin intervenes

Message Flow in Postfix (1)

- Example


- helene@oreilly.com => frank@postfix.org (doel@onlamp.com)
- Phase 1:
 - Helene compose mail using her MUA, and then call postfix's sendmail command to send it



Message Flow in Postfix (2)


- Example

- frank@postfix.org => doel@onlamp.com
- Phase2:
 - The smtpd on postfix.org takes this message and invoke cleanup then put in incoming queue
 - The local DA find that frank is an alias, so it resubmits it through cleanup daemon for further delivery



Message Flow in Postfix (3)

- Example
 - frank@postfix.org => doel@onlamp.com
 - Phase3
 - The smtpd on onlamp.com takes this message and invoke cleanup then put in incoming queue
 - Local delivery to message store



Message Store Format



- The Mbox format
 - Store messages in **single file** for each user
 - Each message start with "**From**" line and continued with message headers and body
 - Mbox format has **file-locking** problem (performance)
- The Maildir format
 - Use **structure of directories** to store email messages
 - Each message is in its owned file
 - Three subdirectories - cur, new, and tmp
 - cur: already read
 - new: unread
 - tmp: under receiving (working dir)
 - Maildir format has **scalability** problem
 - locate and delete mails quickly, but waste amounts of fd, inodes, space
 - Problems of quota and backup
- Related parameters (in main.cf)
 - mail_spool_directory = /var/mail (Mbox)
 - mail_spool_directory = /var/mail/ (Maildir)

Read your mail from terminal

- To read mails, you must login via ssh
 - Built-in command to read mail: "mail"
 - Friendly command-line MUA: "mutt"
 - Pkg: mutt
 - Port: mail/mutt
- To read from remote host
 - Supports MUA like Outlook, Thunderbird, or even Gmail
 - You need MAA (supports IMAP/POP3)
 - Dovecot
 - Pkg: dovecot
 - Port: mail/dovecot

Postfix & POP3/IMAP

- POP3 vs. IMAP
 - Both are used to retrieve mail from server for remote clients
 - POP3 has to download entire message, while IMAP can download headers only
 - POP3 can download only single mailbox, while IMAP can let you maintain multiple mailboxes and folders on server
- Postfix works together with POP3/IMAP
 - Postfix and POP3/IMAP must agree on the type of **mailbox** format and style of **locking**
 - Standard message store
 - Non-standard message store
 - Such as Cyrus IMAP or Dovecot



Postfix Configuration

- Two most important configuration files
 - /usr/local/etc/postfix/main.cf – postconf(5)
 - Core configuration
 - /usr/local/etc/postfix/master.cf – master(5)
 - Which postfix service should invoke which program
- Edit main.cf
 - Using text editor
 - postconf
 - \$ postconf [-e] "myhostname=nasa.cs.nctu.edu.tw"
 - \$ postconf -d myhostname (print default setting)
 - \$ postconf myhostname (print current setting)
- Reload postfix whenever there is a change
 - \$ postfix reload

Postfix Configuration – Lookup tables (1)

- Parameters that use external files to store values
 - Such as mydestination, mynetwork, relay_domains
 - Text-based table is ok, but time-consuming when table is large
- Lookup tables syntax
 - Key values
- Database format
 - \$ postconf -m
 - List all available database format
 - In main.cf
 - default_database_type

```
$ postconf default_database_type
default_database_type = hash
$ postconf -h default_database_type
hash
```

```
% postconf -m
btree
cidr
environ
hash
internal
proxy
regexp
static
tcp
texthash
unix
```

Postfix Configuration – Lookup tables (2)

- Use databased-lookup table in main.cf

- syntax

- parameter = type:name

- E.g.

- In main.cf

- canonical_maps = hash:/usr/local/etc/postfix/canonical

- After execute postmap

- /usr/local/etc/postfix/canonical.db

- postmap command

- Generate database

- \$ postmap hash:/usr/local/etc/postfix/canonical

- Query

- \$ postmap -q nctu.edu.tw hash:/usr/local/etc/postfix/canonical

don't need to add ".db" here

Postfix Configuration – Lookup tables (3)

- Regular expression tables
 - More flexible for matching keys in lookup tables
 - Sometimes you cannot list all the possibilities
 - Two regular expression libraries used in Postfix
 - POSIX extended regular expression (regexp, default)
 - Perl-Compatible regular expression (PCRE)
 - Usage
 - /pattern/ value
 - Do some content checks (filtering)
 - header_checks
 - body_checks
 - Design some features
 - `/(\S+)\.(\S+)@cs\.nctu\.edu\.tw/ $1@cs.nctu.edu.tw`

Postfix Configuration – Categories

- Categories
 - Server identities
 - my...
 - Mail rewriting
 - for incoming/outgoing mails
 - Access control
 - restrictions
 - Mail processing
 - filter
 - Operation details
 - ...

Postfix Configuration – MTA Identity

- Four related parameters
 - myhostname
 - myhostname = nasa.cs.nctu.edu.tw
 - If un-specified, postfix will use 'hostname' command
 - mydestination
 - List all the domains that postfix should accept for local delivery
 - mydestination = \$myhostname, localhost.\$mydomain \$mydomain
 - This is the CS situation that MX will route mail to mailgate
 - mydestination = \$myhostname www.\$mydomain, ftp.\$mydomain
 - mydomain
 - mydomain = cs.nctu.edu.tw
 - If un-specified, postfix use myhostname minus the first component
 - myorigin
 - myorigin = \$mydomain (default is \$myhostname)

Postfix Configuration – System-wide aliases

- Using aliases in Postfix (**first-matching**)
 - alias_maps = hash:/etc/aliases
 - alias_maps = hash:/etc/aliases, nis:mail.aliases
 - alias_database = hash:/etc/aliases
- alias_map vs alias_database
 - alias_map
 - Which map to use (lookup table)
 - Not all of them is controlled by Postfix
 - E.g. nis
 - alias_database
 - Tell "newaliases" which (local) database to rebuild

Postfix Configuration – System-wide aliases

- To Build alias database file
 - \$ postalias /etc/aliases
 - Can be used on files other than /etc/aliases
 - \$ newaliases
 - For /etc/aliases => can be changed by "alias_database"
- Alias file format (same as sendmail)
 - Value can be
 - Email address, filename, |command, :include:
- Alias restriction (alias, forward, include)
 - allow_mail_to_commands = alias, forward
 - allow_mail_to_files = alias, forward

Postfix Configuration – Virtual Alias Maps

Postfix Configuration – Virtual Alias Maps vs Alias Map

- alias_map
 - Used by [local\(8\)](#) delivery
 - Key must be local recipients
 - Value can be email/file/command/...
- virtual_alias_maps
 - Used by [virtual\(5\)](#) delivery
 - Higher priority than alias_map
 - Key can be
 - user@domain
 - user
 - @domain
 - Value must be valid email addresses or local recipients

Postfix Configuration – Relay Control (1)

- Open relay
 - A mail server that permit anyone to relay mails
 - Neither originates or ends with a user from its domain
 - **Spam**
 - By default, postfix is not an open relay
- A mail server should
 - Relay mail for trusted user
 - Such as `lctseng@smtp.cs.nctu.edu.tw`
 - Relay mail for trusted domain
 - E.g. `smtp.cs.nctu.edu.tw` trusts `cs.nctu.edu.tw`

Postfix Configuration – Relay Control (2)

- Restricting relay access by mynetworks_style
 - mynetworks_style = subnet
 - Allow relaying from other hosts in the same **subnet**, configured in this machine
 - mynetworks_style = host
 - Allow relaying for only local machine
 - mynetworks_style = class
 - Any host in the same class A, B or C
 - Usually we don't use this - your server may trust the whole subnet from your provider

Postfix Configuration – Relay Control (3)

- Restricting relay access by mynetworks (override mynetworks_style)
 - List individual IP or subnets in network/netmask notation
 - E.g. in /usr/local/etc/postfix/mynetworks
 - 127.0.0.0/8
 - 140.113.0.0/16
 - 10.113.0.0/16
- Relay depends on the type of your mail server
 - smtp.cs.nctu.edu.tw will be different from csmx1.cs.nctu.edu.tw
 - Outgoing: usually accepts submission from local domain
 - Incoming: may relay mails for trusted domains

Postfix Configuration – Rewriting address (1)

- For unqualified address
 - To append "myorigin" to local name
 - lctseng => lctseng@**nasa.cs.nctu.edu.tw**
 - append_at_myorigin = yes
 - To append "mydomain" to address that contain only host.
 - lctseng@nasa=> lctseng@**nasa.cs.nctu.edu.tw**
 - append_dot_mydomain = yes

Postfix Configuration – Rewriting address (2)

- Masquerading hostname
 - Hide the names of internal hosts to make all addresses appear as if they come from the same mail server
 - It is often used in out-going mail gateway
 - masquerade_domains = cs.nctu.edu.tw
 - lctseng@subdomain.cs.nctu.edu.tw => lctseng@cs.nctu.edu.tw
 - masquerade_domains = !chairman.cs.nctu.edu.tw cs.nctu.edu.tw
 - masquerade_exceptions = admin, root
 - Rewrite to all envelope and header address **excepts envelope recipient** address (the default)
 - masquerade_class = envelope_sender, header_sender, header_recipient
 - This allows incoming messages can be filtered based on their recipient address

Postfix Configuration – Rewriting address (3)

- Canonical address – canonical(5)
 - Rewrite both **header** and **envelope recursively** invoked by **cleanup** daemon
 - In main.cf
 - canonical_maps = hash:/usr/local/etc/postfix/canonical
 - canonical_classes = envelope_sender, envelope_recipient, header_sender, header_recipient
 - In canonical

```
/^(.*@(t)?(cs)?(bsd|linux|sun)\d*\.\cs\.\nctu\.\edu\.\tw$/      $1@cs.nctu.edu.tw
```
 - Similar configurations
 - sender_canonical_maps 、 sender_canonical_classes
 - recipient_canonical_maps 、 recipient_canonical_classes

Postfix Configuration – Rewriting address (4)

- Relocated users

- Used to inform sender that the recipient is moved
 - "user has moved to *new_location*" bounce messages
- In main.cf
 - `relocated_maps = hash:/usr/local/etc/postfix/relocated`
- In relocated

`andy@nasa.cs.nctu.edu.tw` `andyliu@abc.com`

`lctseng` `EC319, NCTU, Hsinchu, ROC`

`@nbsd.cs.nctu.edu.tw` `zfs.cs.nctu.edu.tw`

- Unknown users

- Not local user and not found in maps
- Default action: reject

Value can be anything: phone number, street address, ...

Postfix Configuration – master.cf (1)

- /usr/local/etc/postfix/master.cf (**master(5)**)

- Define services that **master** daemon can invoke
- Each row defines a service and
- Each column contains a specific configuration option

```
# =====
# service type  private unpriv  chroot  wakeup  maxproc command + args
#           (yes)   (yes)   (yes)   (never) (100)
# =====
smtp      inet  n      -       n       -       -       smtpd
pickup    unix  n      -       n       60      1       pickup
cleanup   unix  n      -       n       -       0       cleanup
rewrite   unix  -      -       n       -       -       trivial-rewrite
smtp      unix  -      -       n       -       -       smtp
local    unix  -      n      n      -       -       local
virtual  unix  -      n      n      -       -       virtual
relay    unix  -      -       n       -       -       smtp
               -o smtp_fallback_relay=
lmtp     unix  -      -       n       -       -       lmtp
maildrop  unix  -      n      n      -       -       pipe
flags=DRhu user=vmail argv=/usr/local/bin/maildrop -d ${recipient}
```

Postfix Configuration – master.cf (2)

- Configuration options
 - Service name
 - Service type
 - inet, unix, fifo (obsolete), or pass
 - Private
 - Access to this component is restricted to the Postfix system
 - "inet" type cannot be private
 - Unprivileged
 - Run with the least amount of privilege required
 - y will run with the account defined in "mail_owner"
 - n will run with root privilege
 - local, pipe, spawn, and virtual

Postfix Configuration – master.cf (3)

- Configuration options
 - Chroot
 - chroot location is defined in "queue_directory"
 - Wake up time
 - Automatically wake up the service after the number of seconds
 - Process limit
 - Number of processes that can be executed simultaneously
 - Default count is defined in "default_process_limit"
 - command + args
 - Default path is defined in "daemon_directory"
 - /usr/libexec/postfix

Postfix Architecture – Message OUT

- Local delivery
- Relay to the destinations
- Other delivery agent (MDA)
 - Specify in /usr/local/etc/postfix/master.cf
 - How a client program connects to a service and what daemon program runs when a service is requested
 - lmtp
 - Local Mail Transfer Protocol (Limited SMTP)
 - No queue
 - One recipient at once
 - Used to deliver to mail systems on the same network or even the same host
 - pipe
 - Used to deliver message to external program

Mail Relaying – Transport Maps (1)

- Transport maps – transport(5)
 - It **override default** transport method to deliver messages
 - In main.cf
 - `transport_maps = hash:/usr/local/etc/postfix/transport`
 - In transport file  "Service" defined in master.cf
 - `domain_or_address transport:nexthop`

csie.nctu.edu.tw `smtp:[mailgate.csie.nctu.edu.tw]`

cs.nctu.edu.tw `smtp:[csmailgate.cs.nctu.edu.tw]`

cis.nctu.edu.tw `smtp:[mail.cis.nctu.edu.tw]`

example.com `smtp:[192.168.23.56]:20025`

orillynet.com `smtp`


ora.com `maildrop`

kdent@ora.com `error:no mail accepted for kdent`

Mail Relaying – Transport Maps (2)


Mail Relaying – Inbound Mail Gateway (1)

- Inbound Mail Gateway (IMG, MX)
 - Accept all mail for a network from the Internet and relays it to internal mail systems
 - E.g.
 - gw.example.com is a IMG
 - With MX records
 - mail1.example.com is internal mail system
 - Serves internal subnet



Mail Relaying – Inbound Mail Gateway (2)


- To be IMG, suppose
 - You are administrator for cs.nctu.edu.tw
 - Hostname is csmx1.cs.nctu.edu.tw
 - You have to be the IMG for secureLab.cs.nctu.edu.tw and javaLab.cs.nctu.edu.tw
 - Firewall only allow outsource connect to IMG port 25
- 1. The MX record for secureLab.cs.nctu.edu.tw and javaLab.cs.nctu.edu.tw should point to csmx1.cs.nctu.edu.tw
- 2. In csmx1.cs.nctu.edu.tw,
`relay_domains = secureLab.cs.nctu.edu.tw javaLab.cs.nctu.edu.tw
transport_maps = hash:/usr/local/etc/postfix/transport
secureLab.cs.nctu.edu.tw relay:[secureLab.cs.nctu.edu.tw]
javaLab.cs.nctu.edu.tw relay:[javaLab.cs.nctu.edu.tw]`
- 3. In secureLab.cs.nctu.edu.tw (and so do javaLab.cs.nctu.edu.tw)
`mydestination = secureLab.cs.nctu.edu.tw`



Mail Relaying – Outbound Mail Gateway


- Outbound Mail Gateway
 - Accept mails from inside network and relay them to Internet hosts
- To be OMG, suppose
 - You are administrator for cs.nctu.edu.tw
 - Hostname is csmailer.cs.nctu.edu.tw
 - You have to be the OMG for secureLab.cs.nctu.edu.tw and javaLab.cs.nctu.edu.tw
- 1. In main.cf of csmailer.cs.nctu.edu.tw
`mynetworks = hash:/usr/local/etc/postfix/mynetworks`

`secureLab.cs.nctu.edu.tw`
`javaLab.cs.nctu.edu.tw`
- 2. All students in secureLab/javaLab will configure their MUA to use secureLab/javaLab.cs.nctu.edu.tw to be the SMTP server
- 3. In main.cf of secureLab/javaLab.cs.nctu.edu.tw,
`relayhost = [csmailer.cs.nctu.edu.tw]`



Queue Management

- The queue manage daemon
 - qmgr daemon
 - Unique queue ID
 - Queue directories (/var/spool/postfix/*)
 - active, bounce, corrupt, deferred, hold
- Message movement between queues
 - Temporary problem => deferred queue
 - qmgr takes messages alternatively between incoming and deferred queue to active queue



Queue Management – Queue Scheduling

- Double delay in deferred messages
 - Between
 - `minimal_backoff_time` = 300s
 - `maximal_backoff_time` = 4000s
 - qmgr daemon periodically scan deferred queue for reborn messages
 - `queue_run_delay` = 300s
- Deferred => bounce
 - `maximal_queue_lifetime` = 5d

Queue Management – Message Delivery

- Controlling outgoing messages
 - When there are lots of messages in queue for the same destination, it should be careful not to overwhelm it
 - If concurrent delivery is success, postfix can increase concurrency between:
 - initial_destination_concurrency = 5
 - default_destination_concurrency_limit = 20
 - Under control by
 - maxproc in /usr/local/etc/postfix/master.cf
 - You can override the default_destination_concurrency_limit for any transport mailer:
 - smtp_destination_concurrency_limit = 25 **for external delivery**
 - local_destination_concurrency_limit = 10 **for local recipients**
 - Control how many recipients for a single outgoing message
 - default_destination_recipient_limit = 50
 - You can override it for any transport mailer in the same idea:
 - smtp_destination_recipient_limit = 100

Queue Management – Error Notification

- Sending error messages to administrator
 - Set notify_classes parameter to list error classes that should be generated and sent to administrator
 - Ex: notify_classes = resource, software
 - Error classes

| Error Class | Description | Noticed Recipient (all default to postmaster) |
|-------------|---|--|
| bounce | Send headers of bounced mails | bounce_notice_recipient |
| 2bounce | Send undeliverable bounced mails | 2bounce_notice_recipient |
| delay | Send headers of delayed mails | delay_notice_recipient |
| policy | Send transcript when mail is reject due to anti-spam restrictions | error_notice_recipient |
| protocol | Send transcript that has SMTP error | error_notice_recipient |
| resource | Send notice because of resource problem | error_notice_recipient |
| software | Send notice because of software problem | error_notice_recipient |


Queue Management – Queue Tools (1)

- postqueue(1)

- postqueue -p (or mailq)
 - Show the queued mails (with information like message ID, but not **mail content**)
- postqueue -f
 - Attempt to flush(deliver) all queued mail
- postqueue -s cs.nctu.edu.tw
 - Schedule immediate delivery of all mail queued for site

- postsuper(1)

- Delete queued messages
 - postsuper -d E757A3428C6 (from incoming, active, deferred, hold)
 - postsuper -d ALL
- Put messages "on hold" so that no attempt is made to deliver it
 - postsuper -h E757A3428C6 (from incoming, active, deferred)
- Release messages in hold queue (into deferred queue)
 - postsuper -H ALL
- Requeue messages into maildrop queue (maildrop => pickup => cleanup => incoming)
 - postsuper -r E757A3428C6
 - postsuper -r ALL



Queue Management – Queue Tools (2)

- postcat(1)

- Display the contents of a queue file

```
nasa [/home/lctseng] -lctseng- mailq
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----
3314234284A      602 Sat May 19 04:16:20 root@nasa.cs.nctu.edu.tw
                  (connect to csmx1.cs.nctu.edu.tw[140.113.235.104]:25: Operation timed out)
lctseng@cs.nctu.edu.tw

nasa [/home/lctseng] -lctseng- sudo postcat -q 3314234284A
*** ENVELOPE RECORDS deferred/3/3314234284A ***
message_size:          602           214           1           0           602
message_arrival_time: Sat May 19 04:16:20 2012
create_time:   Sat May 19 04:16:20 2012
sender:       root@nasa.cs.nctu.edu.tw
named_attribute: rewrite_context=local
original_recipient: root
recipient:    lctseng@cs.nctu.edu.tw
*** MESSAGE CONTENTS deferred/3/3314234284A ***
Received: by nasa.cs.nctu.edu.tw (Postfix)
          id 3314234284A; Sat, 19 May 2012 04:16:20 +0800 (CST)
Delivered-To: root@nasa.cs.nctu.edu.tw
Received: by nasa.cs.nctu.edu.tw (Postfix, from userid 0)
          id 2CB713427A5; Sat, 19 May 2012 04:16:20 +0800 (CST)
To: root@nasa.cs.nctu.edu.tw
Subject: nasa.cs.nctu.edu.tw weekly run output
Message-Id: <20120518201620.2CB713427A5@nasa.cs.nctu.edu.tw>
Date: Sat, 19 May 2012 04:16:20 +0800 (CST)
From: root@nasa.cs.nctu.edu.tw (NASA Root)

Rebuilding locate database:
Rebuilding whatis database:
...
```

Multiple Domains

- Use single system to host many domains
 - E.g.
 - We use csmailto.cs.nctu.edu.tw to host both **cs.nctu.edu.tw** and **csie.nctu.edu.tw**
 - Purpose
 - Final delivery on the machine
 - Forwarding to destination elsewhere (mail gateway)
- Important considerations
 - Does the same user id with different domain should go to the same mailbox or different mailbox?
 - YES (shared domain)
 - NO (separate domain)
 - Does every user require a system account in /etc/passwd ?
 - YES (system account)
 - NO (virtual account)

Multiple Domains – Shared Domain with System Account

- Situation
 - The mail system should accept mails for both canonical and virtual domains and
 - The same mailbox for the same user id (`lctseng@` => `/var/mail/lctseng`)
- Procedure
 - Setup MX records for both domains
 - Modify "mydomain" to canonical domain
 - Modify "mydestination" parameter to let mails to virtual domain can be local delivered
 - E.g.
 - `mydomain = cs.nctu.edu.tw`
 - `mydestination = $myhostname, $mydomain, csie.nctu.edu.tw`
 - ※ In this way, mail to both lctseng@cs.nctu.edu.tw and lctseng@csie.nctu.edu.tw will go to `csmailgate:/var/mail/lctseng`
- Limitation
 - Can not separate lctseng@cs.nctu.edu.tw from lctseng@csie.nctu.edu.tw

Multiple Domains – Separate Domains with System Accounts

- Situation
 - The mail system should accept mails for both canonical and virtual domains
 - Mailboxes are not necessarily the same for the same user id
- Procedure
 - Modify "mydomain" to canonical domain
 - Modify "virtual_alias_domains" to accept mails to virtual domains
 - Create "virtual_alias_maps" map
 - E.g.
 - mydomain = cs.nctu.edu.tw
 - virtual_alias_domains = abc.com.tw, xyz.com.tw
 - virtual_alias_maps = hash:/usr/local/etc/postfix/virtual
- Limitation
 - Need to maintain system accounts for virtual domain users

| | |
|-------------------------------|--------------|
| CEO@abc.com.tw @xyz.com.tw | andy jack |
|-------------------------------|--------------|



Multiple Domains –

Separate Domains with Virtual Accounts (1)

- Useful when users in virtual domains:
 - Do not need to login to system
 - Only need to retrieve mail through POP/IMAP server
- Procedure
 - Modify "virtual_mailbox_domains" to let postfix know what mails it should accept
 - Modify "virtual_mailbox_base" and create related directory to put mails
 - Create "virtual_mailbox_maps" map
 - E.g.
 - virtual_mailbox_domain = abc.com.tw, xyz.com.tw
 - virtual_mailbox_base = /var/vmail
 - Create /var/vmail/abc-domain and /var/vmail/xyz-domain
 - virtual_mailbox_maps = hash:/usr/local/etc/postfix/vmailbox
 - In /usr/local/etc/postfix/vmailbox
 - CEO@abc.com.tw abc-domain/CEO (Mailbox format)
 - CEO@xyz.com.tw xyz-domain/CEO/ (Maildir format)

Multiple Domains –

Separate Domains with Virtual Accounts (2)

- Ownerships of virtual mailboxes
 - Simplest way:
 - The same owner of POP/IMAP Servers
 - Flexibility in postfix
 - `virtual_uid_maps` and `virtual_gid_maps`
 - E.g.
 - `virtual_uid_maps = static:1003`
 - `virtual_gid_maps = static:105`
 - `virtual_uid_maps = hash:/usr/local/etc/postfix/virtual_uids`
 - `virtual_uid_maps = hash:/usr/local/etc/postfix/virtual_uids static:1003`
 - In `/usr/local/etc/postfix/virtual_uids`
 - CEO@abc.com.tw 1004
 - CEO@xyz.com.tw 1008

Step by Step Examples

Let's learn from examples

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

Step by Step Examples


- Build a Basic MTA
 - Send test mails to verify your MTA
 - Check whether your mail is sent or not
- MTA Authentication
- MTA Encryption
- MAA for POP3 and IMAP
- Note
 - In this example, we assume you have public IP/domain

Build a Basic MTA

Can send mails to other domain

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU



Build a basic MTA(1)

- Can send mails to other domain
- Install Postfix
 - Pkg: postfix
 - Port: mail/postfix
- After installation
 - Disable "sendmail" program
 - service sendmail stop
 - In /etc/rc.conf
 - `sendmail_enable="NONE"`
 - In /etc/periodic.conf (create if not exists)

```
daily_clean_hoststat_enable="NO"
daily_status_mail_rejects_enable="NO"
daily_status_include_submit_mailq="NO"
daily_submit_quererun="NO"
```

Build a basic MTA(2)

- Replace sendmail by Postfix modified version
 - Edit /etc/mail/mailer.conf

```
Sendmail    /usr/local/sbin/sendmail
send-mail   /usr/local/sbin/sendmail
Mailq       /usr/local/sbin/sendmail
newaliases  /usr/local/sbin/sendmail
```

Build a basic MTA(3)

- After installation
 - Enable postfix
 - Edit /etc/rc.conf
 - postfix_enable="YES"
 - service postfix start
- Set up DNS records
 - Some domains will reject mails from hosts without DNS record
 - Suppose the hostname is "demo1.nasa.lctseng.nctucs.net"
 - Set up these records
 - (A record) demo1.nasa.lctseng.nctucs.net
 - (A record) nasa.lctseng.nctucs.net
 - (MX record) nasa.lctseng.nctucs.net
 - Points to "demo1.nasa.lctseng.nctucs.net"

Build a basic MTA(4)

- Set up MTA identity
 - In main.cf

```
myhostname = demo1.nasa.lctseng.nctucs.net
mydomain = nasa.lctseng.nctucs.net
myorigin = $myhostname
mydestination = $myhostname, localhost. $mydomain,
                localhost, $mydomain
```

- Reload or restart postfix to apply changes
 - \$ postfix reload

Send test mails to verify your MTA(1)

- "telnet" or "mail" command

```
> telnet localhost 25
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^>'.
220 demo1.nasa.lctseng.nctucs.net ESMTP Postfix
EHLO localhost
250-demo1.nasa.lctseng.nctucs.net
250-PIPELINING
250-SIZE 10240000
250-VRFY
250-ETRN
250-ENHANCEDSTATUSCODES
250-8BITMIME
250 DSN
MAIL FROM: lctseng@nasa.lctseng.nctucs.net
250 2.1.0 Ok
RCPT TO: lctseng@cs.nctu.edu.tw
250 2.1.5 Ok
DATA
354 End data with <CR><LF>.<CR><LF>
Subject: This is test mail

DATA
.
250 2.0.0 Ok: queued as 3C868150
```

telnet

Send test mails to verify your MTA(2)


- The "mail" command

```
> mail -s "test from nasa" lctseng@gmail.com
This is test mail from NASA
regards,
admin
(Press Ctrl+D)
```

mail

- See man page for more details

- Result (gmail)



Send test mails to verify your MTA(3)

- Mail source text of the previous example

```
Delivered-To: lctseng@gmail.com
Received: by 10.129.125.135 with SMTP id y129csp874822ywc;
          Sun, 6 Mar 2016 02:39:22 -0800 (PST)
X-Received: by 10.98.87.90 with SMTP id 187mr25639644pf.70.1457260762400;
          Sun, 06 Mar 2016 02:39:22 -0800 (PST)
Return-Path: <lctseng@nasa.lctseng.nctucs.net>
Received: from demo1.nasa.lctseng.nctucs.net ... (omitted)
          by mx.google.com with ESMTP id bz6si20406744pad.30.2016.03.06.02.39.21
          for <lctseng@gmail.com>;
          Sun, 06 Mar 2016 02:39:21 -0800 (PST)
Received-SPF: neutral (google.com: 140.113.168.238 is neither permitted ... (omitted)
Authentication-Results: mx.google.com;
          spf=neutral (google.com: 140.113.168.238 is neither permitted ... (omitted)
Received: by demo1.nasa.lctseng.nctucs.net (Postfix, from userid 1001)
          id 6D916162; Sun, 6 Mar 2016 18:38:04 +0800 (CST)
To: lctseng@gmail.com
Subject: test from nasa
Message-Id: <20160306103804.6D916162@demo1.nasa.lctseng.nctucs.net>
Date: Sun, 6 Mar 2016 18:38:04 +0800 (CST)
From: lctseng@nasa.lctseng.nctucs.net (lctseng)

This is test mail from NASA
regards,
admin
```

Check whether your mail is sent or not (1)

- Sometimes, we do not receive mails immediately
 - There may be some errors when your MTA sending mails to other domain
- Mails will stay in queues
 - Contain information about each mail
- Tools to management mail queues
 - postqueue
 - postsuper

Check whether your mail is sent or not (2)

- Example for rejected mails (send mails to `@cs.nctu.edu.tw`)

```
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----  
3C868150          377 Sun Mar  6 18:23:11 lctseng@nasa.lctseng.nctucs.net  
(host csmx3.cs.nctu.edu.tw[140.113.235.119] said: 450 4.1.8  
<lctseng@nasa.lctseng.nctucs.net>: Sender address rejected: Domain not found  
(in reply to RCPT TO command) lctseng@cs.nctu.edu.tw  
  
-- 0 Kbytes in 1 Request.
```

- Problem
 - The destination MX cannot verify the **domain of sender host**
- Reason
 - You may forget to set up correct DNS record
- This mail will **NOT** be delivered until you set up your DNS record

Check whether your mail is sent or not (3)

- Example for deferred mails

```
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----  
3C868150      377 Sun Mar  6 18:23:11 lctseng@nasa.lctseng.nctucs.net  
(host csmx1.cs.nctu.edu.tw[140.113.235.104] said: 450 4.2.0  
<lctseng@cs.nctu.edu.tw>: Recipient address rejected: Greylisted,  
see http://postgrey.schweikert.ch/help/cs.nctu.edu.tw.html  
(in reply to RCPT TO command))    lctseng@cs.nctu.edu.tw  
  
-- 0 Kbytes in 1 Request.
```

- Problem
 - The mail is deferred for a short time
- Reason
 - Destination host wants to examine our server is a spamming host or not
- The mail will be delivered after a short time
 - Generally within 30 minutes

MTA Authentication

We don't want unauthorized user to access our MTA

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

MTA authentication(1)

- In previous example, only localhost can send mail to other domain
- If you try telnet on other host, when you try to send mails to other domain, you will get:

```
> telnet demo1.nasa.lctseng.nctucs.net 25
Trying 140.113.168.238...
Connected to demo1.nasa.lctseng.nctucs.net.
Escape character is '^]'.
220 demo1.nasa.lctseng.nctucs.net ESMTP Postfix
MAIL FROM: lctseng@demo1.nasa.lctseng.nctucs.net
250 2.1.0 Ok
RCPT TO: lctseng@gmail.com
454 4.7.1 <lctseng@gmail.com>: Relay access denied
```

- That is because you have following lines (default) in main.cf

```
mynetworks_style = host
```

- So Postfix only trust clients from localhost

MTA authentication(2)

- How to let SMTP clients outside from trust networks get the same privileges as trusted hosts?
 - Can send mails to other domain, not only **\$mydestination**
 - We need authentication (account and password)
- SASL Authentication
 - Simple Authentication and Security Layer
 - [RFC 2554](#), [RFC 4954](#)
- To configure SASL for Postfix, we need another daemon
 - Dovecot SASL (we use it in our example)
 - Cyrus SASL (need to enable it by port)
- References
 - <http://wiki2.dovecot.org/>
 - http://www.postfix.org/SASL_README.html

MTA authentication(3) - Dovecot SASL

- Installation
 - Pkg: dovecot
 - Port: mail/dovecot
- Enable Dovecot SASL daemon
 - In /etc/rc.conf
 - `dovecot_enable="YES"`
 - Copy configuration files
 - `cp -R /usr/local/etc/dovecot/example-config/* \ /usr/local/etc/dovecot`
 - Create SSL keys for Dovecot (self-signed or use Let's Encrypt)
 - Change path for SSL files in `/usr/local/etc/dovecot/conf.d/10-ssl.conf`
 - Note: these are mainly for POP3s and IMAPs, not SASL in Postfix
 - service dovecot start

MTA authentication(4) - Postfix with Dovecot SASL

- Set up Dovecot SASL authenticate (using system account)
 - In /usr/local/etc/dovecot/conf.d/10-master.conf:

```
service auth {  
    ...  
    # Postfix smtp-auth  
    unix_listener /var/spool/postfix/private/auth {  
        mode = 0666  
    }  
    ...  
}
```

- In /usr/local/etc/dovecot/conf.d/10-auth.conf

```
auth_mechanisms = plain login
```

MTA authentication(5) - Postfix with Dovecot SASL

- Set up Dovecot SASL in Postfix
 - In main.cf

```
# Set SASL to Dovecot
smtpd_sasl_type = dovecot
# Specify the UNIX socket path
smtpd_sasl_path = private/auth
# Enable SASL
smtpd_sasl_auth_enable = yes
# For client (backward) capability
broken_sasl_auth_clients = yes
# Allow SASL authenticated clients
smtpd_recipient_restrictions = permit_mynetworks,
                                permit_sasl_authenticated,
                                reject_unauth_destination
```

- Restart/Reload Dovecot and Postfix

MTA authentication(6)

- Now you can authenticate your identity in SMTP

```
> telnet demo1.nasa.lctseng.nctucs.net 25
Trying 140.113.168.238...
Connected to demo1.nasa.lctseng.nctucs.net.
Escape character is '^]'.
220 demo1.nasa.lctseng.nctucs.net ESMTP Postfix
EHLO linuxhome.cs.nctu.edu.tw
250-demo1.nasa.lctseng.nctucs.net
250-PIPELINING
250-SIZE 10240000
250-VRFY
250-ETRN
250-AUTH PLAIN LOGIN
250-AUTH=PLAIN LOGIN
250-ENHANCEDSTATUSCODES
250-8BITMIME
250 DSN
```

MTA authentication(7)

- The account and password are encoded in Base64
 - If you have perl installed, suggest your account is **test** and password is **testpassword**

```
perl -MMIME::Base64 -e 'print encode_base64("\000test\000testpassword");'
```
 - It will generate encoded account and password
 - For example: AHRlc3QAdGVzdHBhc3N3b3Jk

MTA authentication(8)

- Use the encoded account and password to authenticate it

```
> telnet demo1.nasa.lctseng.nctucs.net 25
Trying 140.113.168.238...
Connected to demo1.nasa.lctseng.nctucs.net.
Escape character is '^]'.
220 demo1.nasa.lctseng.nctucs.net ESMTP Postfix
AUTH PLAIN AHRlc3QAdGVzdHBhc3N3b3Jk
235 2.7.0 Authentication successful
MAIL FROM: lctseng@nasa.lctseng.nctucs.net
250 2.1.0 Ok
RCPT TO: lctseng@gmail.com
250 2.1.5 Ok
DATA
354 End data with <CR><LF>.<CR><LF>
To: lctseng@gmail.com
Subject: This is authenticated client
Message-Id: <20160307120109.861A9154@demo1.nasa.lctseng.nctucs.net>
Date: Mon, 7 Mar 2016 15:01:09 +0800 (CST)
From: lctseng@demo1.nasa.lctseng.nctucs.net (lctseng)

Test Mail
.
250 2.0.0 Ok: queued as F3D59171
```

MTA Encryption

The Internet is dangerous, we need to protect ourselves from sniffing.

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

MTA encryption(1)

- In previous example, all SMTP sessions are in **plain text**
 - Your encoded authentication information is in danger!
- We need encryption over SSL/TLS
 - Like HTTP can be enhanced to HTTPS
 - Postfix supports two kinds of encryption
 - SMTP over TLS
 - SMTPs
- Before we enable SMTP over TLS (or SMTPs), you need SSL keys and certificates
 - Again, just like HTTPS
 - Self-signed or use Let's Encrypt
 - You can use the same certificates/keys as Dovecot's
 - In main.cf

```
smtpd_tls_cert_file = /path/to/cert.pem  
smtpd_tls_key_file = /path/to/key.pem
```

MTA encryption(2-1) - Set up SMTP over TLS

- Recommended for SMTP encryption
- Use the same port as SMTP (port 25)
- No force encryption
 - Client can choose whether to encrypt mails or not
 - But server can configured to force encryption
- In main.cf
 - No force encryption

```
smtpd_tls_security_level = may
```
 - Force encryption

```
smtpd_tls_security_level = encrypt
```
- Reload Postfix

MTA encryption(2-2) - Set up SMTP over TLS

- Now your server supports SMTP over TLS

```
> telnet demo1.nasa.lctseng.nctucs.net 25
Trying 140.113.168.238...
Connected to demo1.nasa.lctseng.nctucs.net.
Escape character is '^]'.
220 demo1.nasa.lctseng.nctucs.net ESMTP Postfix
EHLO linuxhome.cs.nctu.edu.tw
250-demo1.nasa.lctseng.nctucs.net
250-PIPELINING
250-SIZE 10240000
250-VRFY
250-ETRN
250-STARTTLS
250-ENHANCEDSTATUSCODES
250-8BITMIME
250 DSN
```

- If you use force encryption, you must STARTTLS before sending mails

```
MAIL FROM: lctseng@nasa.lctseng.nctucs.net
530 5.7.0 Must issue a STARTTLS command first
```

MTA encryption(2-3) - Set up SMTP over TLS

- Send mail with STARTTLS
 - You cannot use telnet (plain-text client) anymore
 - Connection becomes encrypted after STARTTLS
 - telnet cannot read encrypted text
- OpenSSL client

```
openssl s_client -connect demo1.nasa.lctseng.nctucs.net:25 -starttls smtp
```

MTA encryption(3-1) - Set up SMTPs

- Alternative way to encrypt SMTP sessions
- Use different port: 465
- Force encryption
- Can coexist with SMTP over TLS
- In master.cf
 - Uncomment these lines

```
smt�      inet  n      -      n      -      -      smtpd
  -o syslog_name=postfix/smt�
  -o smtpd_tls_wrappermode=yes
```
 - This will open port 465 for SMTPs and use "smt�" as syslog name
- Reload Postfix

MTA encryption(3-2) - Set up SMTPs

- Now you can use SSL clients to use SMTPs


- telnet may not work in encrypted sessions
 - SSL client:

```
openssl s_client -connect host:port
```

- Important note**
 - In openssl s_client, DO NOT use capital character "R"
 - "R" is a special command in openssl s_client (for renegotiating)
 - So use "mail from/rcpt to" instead of "MAIL FROM/RCPT TO"
 - For SMTP, they are all the same
 - If you use "R", you will see following output (NOT a part of SMTP)

```
RENEGOTIATING
depth=2 O = Digital Signature Trust Co., CN = DST Root CA X3
verify return:1
depth=1 C = US, O = Let's Encrypt, CN = Let's Encrypt Authority X1
verify return:1
depth=0 CN = nasa.lctseng.nctucs.net
verify return:1
```

MAA for POP3 and IMAP



Read mails from remote host

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

MAA for POP3 and IMAP (1)

- Dovecot already provides POP3 and IMAP services
 - Include SSL versions: POP3s, IMAPS
 - That why we need SSL certificates and keys for Dovecot
- When you activate Dovecot service, these MAA services are also brought up.
- But you cannot access mail directly, you need some configuration
 - Configuration files are in : /usr/local/etc/dovecot/
 - There are many files included by dovecot.conf
 - In conf.d directory
 - Splitting configuration files is easier to management
 - Reference: https://doc.dovecot.org/configuration_manual/quick_configuration/

MAA for POP3 and IMAP (2)

- Dovecot Configuration

- Allow GID = 0 to access mail (optional)
 - By default, Dovecot do not allow users with GID = 0 to access mail. If your users are in wheel group, you need following settings
 - In dovecot.conf

```
first_valid_gid = 0
```
- Specify the mail location (must agrees with Postfix)
 - In conf.d/10-mail.conf

```
mail_location = mbox:~/mail:INBOX=/var/mail/%u
```
- Add authenticate configuration to use PAM module
 - Dovecot use system PAM module to authenticate
 - Allow system users to access mails
 - Create a new file: /etc/pam.d/dovecot

```
auth    required      pam_unix.so
account required      pam_unix.so
```

MAA for POP3 and IMAP (3)

- After restart Dovecot, your MAA is ready
- To check these services, you can use "telnet" or "openssl s_client"
 - POP3: 110
 - POP3s: 995
 - IMAP: 143
 - IMAPS: 993

MAA for POP3 and IMAP (4)

- IMAP + STARTTLS

```
openssl s_client -connect host.example.com:143 -starttls imap
```

- POP3 + STARTTLS

```
openssl s_client -connect host.example.com:110 -starttls pop3
```

- IMAPs

```
openssl s_client -connect host.example.com:993
```

- POP3s

```
openssl s_client -connect host.example.com:995
```

- Sample message from Dovecot when succeed

- POP **+OK Dovecot ready.**
- IMAP

```
* OK [CAPABILITY IMAP4rev1 LITERAL+ SASL-IR LOGIN-REFERRALS  
ID ENABLE IDLE AUTH=PLAIN AUTH=LOGIN] Dovecot ready.
```

MAA for POP3 and IMAP (5)

- Set up MUAs like Outlook or Thunderbird
 - You can see the tutorial in CS mail server, they should be similar to set up your server
 - Settings for Gmail is also available
 - <https://mail.cs.nctu.edu.tw/>

