

Homework 3

File Server & Backup

phlin, rzhung, hslin

國立陽明交大資工系資訊中心

Outline

- HW 3-1: File server
- HW 3-2: Pure-ftpd uploadscript with advance logging
- HW 3-3: ZFS & Backup

HW 3-1: File Server (25%)

HW 3-1: Requirement (1/4)

Use **pure-ftpd** to build a file server; create 3 directories under */home/ftp*

1. */home/ftp/public*:
 - Everyone can **download & upload** file
 - Everyone can **mkdir, rmdir, delete** except anonymous
2. */home/ftp/upload*:
 - Everyone can **upload & download**
 - Everyone can **mkdir** except anonymous
 - Everyone can only **delete & rmdir** their own file or directory except anonymous and sysadm
3. */home/ftp/hidden*:
 - Create a directory called “**treasure**” inside hidden
 - Create a file called “secret” inside *hidden/treasure*
 - Anonymous can't list */home/ftp/hidden* but **can enter *hidden/treasure* and show *hidden/treasure/secret***

HW 3-1:

Create users

1. Create a **system user** "sysadm"
 - Can login by **SSH & FTP**
 - Password is your IP without dots, e.g. password=1011301 when IP=10.113.0.1
 - Full access to */home/ftp* and subdirectories under "ftp"
2. Create two **virtual users** "ftp-vip1", "ftp-vip2"
 - Password is your IP without dots, e.g. password=1011301 when IP=10.113.0.1
 - Can only delete files in */home/ftp/upload* **which are created by themselves**
 - Other file permissions are same as sysadm
3. Anonymous with no password
 - Can't create any directories, and can't delete any files & directories
 - Can't list */home/ftp/hidden* but **can enter *hidden/treasure* and show *hidden/treasure/secret***

HW 3-1:

Other requirements

- Your ftp server should support **Explicit FTP over TLS** (FTPES)
- All accounts except sysadm are **chrooted** (***/home/ftp*** is the root directory)

HW 3-1:

	<u>sysadm</u>		<u>ftp-vip</u>		<u>anonymous</u>	
	<i>public/</i>	<i>upload/</i>	<i>public/</i>	<i>upload/</i>	<i>public/</i>	<i>upload/</i>
upload	✓	✓	✓	✓	✓	✓
download	✓	✓	✓	✓	✓	✓
mkdir	✓	✓	✓	✓	✗	✗
rmdir	✓	✓	✓	▲	✗	✗
delete	✓	✓	✓	▲	✗	✗

✓: full access ▲: only the owner has permission ✗: permission denied

HW 3-1: Log

- Save all ftp log (login, operate ... etc) into /var/log/pureftpd/pureftpd.log
- Filter only ftp login log into /var/log/pureftpd/login.log

Hint: syslog, VerboseLog

```
[rzhung@nfs ~]$ cat /var/log/pureftpd/pureftpd.log
Nov 10 11:40:40 nfs pure-ftpd[33316]: (?@192.168.202.250) [INFO] New connection from
192.168.202.250
Nov 10 11:40:40 nfs pure-ftpd[33316]: (?@192.168.202.250) [INFO] sysadm is now logged in
Nov 10 11:40:40 nfs pure-ftpd[33316]: (sysadm@192.168.202.250) [NOTICE]
/home/ftp//public/non.exe uploaded (15062 bytes, 41.09KB/sec)
Nov 10 11:41:34 nfs pure-ftpd[33316]: (sysadm@192.168.202.250) [NOTICE]
/home/ftp//public/pureftpd.viofile downloaded (102 bytes, 967.11KB/sec)
Nov 10 11:42:34 nfs pure-ftpd[33316]: (sysadm@192.168.202.250) [INFO] Logout.
```

```
[rzhung@nfs ~]$ cat /var/log/pureftpd/login.log
Nov 10 10:22:46 nfs pure-ftpd[33150]: (?@10.113.0.254) [INFO] sysadm is now logged in
Nov 10 11:36:09 nfs pure-ftpd[33290]: (?@192.168.202.250) [INFO] sysadm is now logged in
```


HW 3-1: Grading (14%)

- FTP over TLS (3%)
- sysadm login
 - login from ssh (1%)
 - Full access to “**public**”, “**upload**”, “**hidden**” (3%)
- ftp-vip1, ftp-vip2 login
 - Full access to “**public**”, “**hidden**” (3%)
 - Full access to “**upload**”, but can only delete their own files and directories. (4%)

HW 3-1: Grading (11%)

- Chrooted (*/home/ftp*) all accounts except sysadm (2%)
- Anonymous login
 - Can only upload and download from “*public*”, “*upload*” (2%)
 - Hidden directory “*/home/ftp/hidden*” problem:
can enter but can't retrieve directory listing (3%)
- Log
 - */var/log/pureftpd/pureftpd.log* (1%)
 - */var/log/pureftpd/login.log* (3%)

HW 3-1: Hint

- README
 - */usr/local/share/doc/pure-ftpd/**
- Accounts related
 - Virtual user
 - [pure-pw\(8\)](#)
 - [pure-pwconvert\(8\)](#)
 - README.Virtual-Users
- If `pure-ftpd` is not working
 - Check your pure-ftpd.conf

HW 3-2: pure-ftpd uploadscript With Adv. Logs (35%)

HW 3-2: Requirements-Script (1/6)

- Create an “**uploadscript.sh**” for filtering every file uploaded. (3%)
 - Files with extension **.exe** is violated
 - Move these files to **hidden/.exe** created at HW3-1

```
[rzhung@nfs ~]$ sudo ls /home/ftp/hidden/.exe/  
test.exe
```

- Log violation of uploadscript into **/home/ftp/public/pureftpd.viofile** (2%)
 - Format -
timestamp hostname programname: filename violate file detected. Uploaded by **upload_user**.

```
[rzhung@nfs ~]$ cat /home/ftp/public/pureftpd.viofile  
Nov 10 11:41:29 nfs ftpusr[33351]: /home/ftp/public/test.exe violate file detected. Uploaded by  
sysadm.
```

HW 3-2: Requirements-Service (2/6)

- Create a service “**ftp-watchd**” which enables running a command after a successful upload (5%)
 - The name of the service should be exactly the same as “ftp-watchd”
 - Execute uploadscript.sh when a file is successfully uploaded to the FTP server
 - Automatically start ftp-watchd when host boots up

HW 3-2: Requirements-Service (3/6)

- `uploadsript` feature in `pure-ftpd` should be activated (5%)
- You should write an `rc` or `systemd` script "`ftp-watchd`" as a daemon to start the `pure-uploadsript` program
 - `pure-uploadsript` should be run in the background when `ftp-watchd` is started
- Your service must support these operation: (5%)
 - `$ service ftp-watchd start`
 - `$ service ftp-watchd stop`
 - `$ service ftp-watchd restart`
 - `$ service ftp-watchd status`

HW 3-2: Requirements-Service (4/6)

- Require a **pid file** to indicate which process to stop

```
[rzhung@nfs ~]$ cat /var/run/pure-uploadsript.pid  
20878
```

- You should display as following format while using each command

- Service start

```
[rzhung@nfs ~]$ sudo service ftp-watchd start  
Starting ftpwatchd.
```

- Service stop

```
[rzhung@nfs ~]$ sudo service ftp-watchd stop  
Kill: 20878
```


HW 3-2: Requirements-Service (5/6)

- Service restart

```
[rzhung@nfs ~]$ sudo service ftp-watchd restart  
Kill: 3458  
Starting ftpwatchd.
```

- Service status

```
[rzhung@nfs ~]$ sudo service ftp-watchd status  
ftpwatchd is running as pid 3477.
```

- More Information: [NASA Forum: Service name]
<https://groups.google.com/g/nctunasa/c/nB5zObRIOLs/m/amrIEuvXBgAJ>

HW 3-2: Requirements-Syslog (6/6)

- Please use **syslog** to handle logs of uploadsript. (10%)
 - “Processname” should be **ftpuscr**
 - Syslog settings for uploadsript should be written in **syslog.d/ftpuscr.conf**
 - To reduce the chance of conflicting with other service logs, please use the “local facility” - `local0` to handle logs.
- All logs should be labeled with proper level (5%)
 - Conditions that are not error conditions, but should possibly be handled specially.

```
[rzhung@nfs ~]$ cat /home/ftp/public/pureftpd.viofile  
Nov 10 11:41:29 nfs ftpuscr[33351]: /home/ftp/public/test.exe violate file detected. Uploaded by  
sysadm.
```

HW 3-2: Grading (Bonus +5%)

- You should finish all basic features before the bonus
- Using the HW3-1 Log section (pureftpd/login.log)
 - Add IP information for logs.

```
[rzhung@nfs ~]$ cat /home/ftp/public/pureftpd.viofile  
Nov 10 11:41:29 nfs ftpuscr[33351]: /home/ftp/public/test.exe violate file detected. Uploaded by  
sysadm. From 192.168.202.250.
```

- Using the latest login log if there is more than one records in pureftpd/login.log

```
[rzhung@nfs ~]$ cat /var/log/pureftpd/login.log  
Nov 10 10:22:46 nfs pure-ftpd[33150]: (?@10.113.0.254) [INFO] sysadm is now logged in  
Nov 10 11:36:09 nfs pure-ftpd[33290]: (?@192.168.202.250) [INFO] sysadm is now logged in
```

HW 3-2: Hint

- Enable upload script under pure-ftpd.conf
 - CallUploadScript yes
- For pure-uploadsript, you can manually start the daemon by following command:
 - `$ pure-uploadsript -B -r /your/uploadsript/to/execute`
- [pure-uploadsript\(8\)](#)

HW 3-3: ZFS & Backup (40%)

Requirements (1/8)

- Enable ZFS service
 - Reboot and everything is fine (ZFS still mounted)
- Add two new hard disks and create a mirror pool called “**mypool**”
 - Mount **mypool** on */home/ftp*
- Create ZFS datasets
 - Set lz4 compression, atime=off to all datasets
 - Create **mypool/public**, **mypool/upload**, **mypool/hidden**

Requirements (2/8)

- Automatic Snapshot Script: **zfsbak**
 - Add your script to \$PATH
 - Allow to execute zfsbak with command "zfsbak ", not "./zfsbak "
 - Usage:
 - Create: zfsbak DATASET [ROTATION_CNT]
 - List: zfsbak -l|--list [DATASET|ID|DATASET ID]
 - Delete: zfsbak -d|--delete [DATASET|ID|DATASET ID]
 - Export: zfsbak -e|--export DATASET [ID]
 - Import: zfsbak -i|--import FILENAME DATASET

```
phlin@nfs:~ % zfsbak
Usage:
- create: zfsbak DATASET [ROTATION_CNT]
- list: zfsbak -l|--list [DATASET|ID|DATASET ID]
- delete: zfsbak -d|--delete [DATASET|ID|DATASET ID]
- export: zfsbak -e|--export DATASET [ID]
- import: zfsbak -i|--import FILENAME DATASET
```

Requirements (3/8)

- Specification - Create (Default)
 - Must specify **dataset**
 - If no rotation count is specified, use 20 as default
 - No more than rotation count snapshots per dataset
 - If rotation count is reached, delete the oldest one
 - Your snapshot should include the dataset name and date
 - When snapshot is the same as previous one, not to do this snapshot {Hint : zfs diff}

```
phlin@nfs:~ % zfsbak -l
ID DATASET TIME
phlin@nfs:~ % sudo zfsbak mypool/public
Snap mypool/public@2021-09-25-17:39:36
phlin@nfs:~ % sudo zfsbak mypool/public
Snap mypool/public@2021-09-25-17:39:40
phlin@nfs:~ % sudo zfsbak mypool/public 1
Snap mypool/public@2021-09-25-17:39:45
Destroy mypool/public@2021-09-25-17:39:36
Destroy mypool/public@2021-09-25-17:39:40
```

```
phlin@nfs:~ % zfsbak -l
ID DATASET TIME
phlin@nfs:~ % sudo zfsbak mypool/public
Snap mypool/public@2021-09-25-17:30:12
phlin@nfs:~ % sudo zfsbak mypool/public
Snapshot is the same as latest one!
phlin@nfs:~ % zfsbak -l
ID DATASET TIME
1 mypool/public 2021-09-25-17:30:12
```


Requirements (4/8)

- Specification – List
 - List snapshots created by zfs. **Sorted by time**
 - If only **ID** is specified, list only the snapshot with that **id**
 - If only **DATASET** is specified, list all snapshots of that dataset
 - If **DATASET** and **ID** are specified, list only the snapshot with that **dataset** and **id**
 - Otherwise, list all snapshots

```
phlin@nfs:~ % zfsbak -l
ID  DATASET      TIME
1   mypool/public 2021-09-25-17:38:12
2   mypool/public 2021-09-25-17:38:45
3   mypool/upload 2021-09-25-18:39:06
4   mypool/upload 2021-09-25-18:39:15
5   mypool/upload 2021-09-25-18:39:22
```

```
phlin@nfs:~ % zfsbak -l 3
ID  DATASET      TIME
3   mypool/upload 2021-09-25-18:39:06
phlin@nfs:~ % zfsbak -l mypool/upload
ID  DATASET      TIME
1   mypool/upload 2021-09-25-18:39:06
2   mypool/upload 2021-09-25-18:39:15
3   mypool/upload 2021-09-25-18:39:22
phlin@nfs:~ % zfsbak -l mypool/upload 2
ID  DATASET      TIME
2   mypool/upload 2021-09-25-18:39:15
```

Requirements (5/8)

- Specification – Delete
 - Delete snapshots created by zfs
 - If only **ID** is specified, delete the dataset with that **id**
 - If only **DATASET** is specified, delete all snapshots of that dataset
 - If **DATASET** and **ID** are specified, delete only the snapshot with that **dataset** and **id**
 - Otherwise, delete all snapshots
 - Can specify multi snapshot and delete

```
phlin@bsdzfs:~ % zfsbak -l
ID  DATASET          TIME
1   mypool/public    2021-09-25-17:55:17
2   mypool/public    2021-09-25-17:55:33
3   mypool/upload    2021-09-25-19:39:27
4   mypool/upload    2021-09-25-19:39:29
5   mypool/upload    2021-09-25-19:39:32
6   mypool/upload    2021-09-25-19:40:37
```

```
phlin@bsdzfs:~ % zfsbak -d 3
Destroy mypool/upload@2021-09-25-19:39:27
phlin@bsdzfs:~ % zfsbak -d mypool/upload 2
Destroy mypool/upload@2021-09-25-19:39:32
phlin@bsdzfs:~ % zfsbak -d mypool/public
Destroy mypool/public@2021-09-25-17:55:17
Destroy mypool/public@2021-09-25-17:55:33
phlin@bsdzfs:~ % zfsbak -d
Destroy mypool/upload@2021-09-25-19:39:29
Destroy mypool/upload@2021-09-25-19:40:37
```

```
phlin@bsdzfs:~ % zfsbak -d mypool/public 1 3 4
Destroy mypool/public@2021-09-25-19:54:49
Destroy mypool/public@2021-09-25-19:55:31
Destroy mypool/public@2021-09-25-19:55:37
```

Requirements (6/8)

- Specification – Export (**Bonus**)
 - Must specify **dataset**
 - **ID** defaults to 1
 - Compress with **gzip**
 - Encrypt with **aes256** (Hint: Use openssl; Ask user to input password)
 - A filename example: `dataset@2021-09-25-20:05:27.gz.enc`
 - Put the export file at the user's home directory.

```
phlin@bsdzfs:~ % sudo zfsbak -e mypool/public 1
enter aes-256-cbc encryption password:
Verifying - enter aes-256-cbc encryption password:
Export mypool/public@2021-09-25-20:05:27 to ~/mypool_public@2021-09-25-20:05:27.gz.enc
```

Requirements (7/8)

- Specification – Import (Bonus)
 - Must specify **filename** and **dataset**
 - **filename** is the file exported by zfsbak
 - Ask user to input password
 - Load the snapshot to the dataset

```
phlin@bsdzfs:~ % sudo zfsbak -i ~/mypool_public@2021-09-25-20:05:27.gz.enc mypool/public2
enter aes-256-cbc encryption password:
Import ~/mypool_public@2021-09-25-20:05:27.gz.enc to mypool/public2
phlin@bsdzfs:~ % zfsbak -l
ID  DATASET          TIME
1   mypool/public    2021-09-25-21:03:27
2   mypool/public    2021-09-25-21:03:35
3   mypool/public2   2021-09-25-21:12:22
phlin@bsdzfs:~ % ls /home/ftp
hidden public public2 upload
```

Requirements (8/8)

- Log
 - Must contain the action (e.g. snap), dataset name and time
 - Print “**Snap `dataset@create_time`**” after creating the new snapshot, e.g.,
 - Snap mypool/public@ 2021-09-25-20:05:27
 - Print “**Destroy `dataset@create_time`**” after destroying the deleted snapshot, e.g.,
 - Destroy mypool/public@ 2021-09-25-20:05:27
 - **(Bonus)** Print “**Export `dataset@create_time` to `file_location`**” after exporting the target snapshot, e.g.,
 - Export mypool/public@2021-09-25-20:05:27 to
~/mypool_public@2021-09-25-20:05:27.gz.enc
 - **(Bonus)** Print “**Import `target_file` to `dataset`**” after importing the target file, e.g.,
 - Import mypool_public@2021-09-25-20:05:27.gz.enc to mypool/public2
 - For any undefined operation, just print the error message and exit

Grading (40/40%, Bonus + 6%)

- Create a mirror storage (2%)
- Create all dataset and set up correctly (2%)
- zfsbak
 - Usage (3%)
 - Create (8%)
 - List (12%)
 - Delete (8%)
 - Log (5%)
 - Export, Import (include log) (Bonus +6%) (Both complete)

Hint

- It will be much easier if you implement `Delete`, `Export`, `Import` with a well coding `List`
- Check handbook first
 - <https://www.freebsd.org/doc/en/books/handbook/zfs-zfs.html>
 - <https://www.freebsd.org/doc/en/books/handbook/zfs-term.html>

Attention!

- Due date: 2021-12-06T23:59:59+08:00
- Online Judge open date: 2021-11-22
- Email us if you finish bonus, we will judge manually
 - ta@nasa.cs.nctu.edu.tw

Help me!

- TA time: 3 GH at EC 324 (PC Lab)
- Questions about this homework
 - Ask them on <https://groups.google.com/g/nctunasa>
 - We MIGHT give out hints on google group
 - Be sure to join the group :D
 - Do not use E3 to email us

Good Luck!